

AERUS PURE & CLEAN AIR AND SURFACE PURIFIER

ActivePure®
TECHNOLOGY

in partnership with

Water Solutions
Long Island



Benefits

- ActivePure® Technology destroys over 99% of all surface and airborne contaminants
- Reduces airborne contaminants and allergens that can trigger asthma and allergy symptoms
- Freshens air and removes odors in otherwise stale-prone environments
- Removes dirt and dust from the air to make cleaning easier
- Portable, no installation required
- Destroys VOCs, smoke and odors
- Inactivates and eliminates viruses and bacteria in the air and on surfaces.
- Meets CDC, FDA, and EPA guidelines for helping to lower the spread of COVID-19

How it works

- Our proprietary **ActivePure® Technology** uses light waves and a catalytic process to produce superoxides, hydroxyl radicals, and hydroperoxides that destroy contaminants in the air and on surfaces
- Features a high intensity UVC light that replicates the same oxidation and ionizing properties of light as naturally occurring sunlight
- Certified Space Technology continuously protects and purifies the environment
- Proven effective in independent studies against bacteria, viruses, mold and fungi in the air and on surfaces

Unique Features

- Positive and Negative Multipoint and RF Ion Generation
- Five Speed Fan
- LCD Display
- Maintenance Reminders
- Replaceable ActivePure® Cells
- Removable Rear Grill
- Universal Power Supply with cords
- HEPA + Activated Carbon filters

Target Customer

- Medical facilities, nursing homes, schools or any facility with indoor air quality concerns
- People who suffer from allergies and asthma
- Those with sensitive immune systems
- Anyone concerned with indoor environmental quality or their health

*eliminated >99.96%
of airborne SARS-CoV-2
in < 3 minutes in a BSL-4
military lab!*



Specifications

Power Consumption	43 Watts
Recommended Treatment Space	300 sq. ft. to 600 sq. ft. (27 m ² to 56 m ²)
Input Voltage	100 ~ 240 VAC; 50/60 Hz external power supply; 43 Amps max
Nominal Airflow Rate	40-60 CFM Fan, Washable electrostatic lint screen
ActivePure® Cell	2 Included
Ozone Production	0.00 ppm with ozone-free replaceable ActivePure® Cell
Dimensions	10" H x 10" W x 12" D (25.4 cm x 25.4 cm x 30.48 cm)
Weight	8 lbs (3.62 kg)
Operating Temperature	34°F – 100°F
Warranty	3 year limited warranty

Meets California ozone emissions limit. CARB Certified. UL 2998



2017 Space Technology Hall
of Fame Inductee

Proudly Designed,
Developed and
Engineered in the United
States of America